

PROJECT:


QUANTITY:

ITEM: NO:

Signature

REFRIGERATED SELF SERVE DISPLAY – DRF-S

MODELS: DRF-S 4840, DRF-S 4848, DRF-S 4860, DRF-S 5178, DRF-S 5194



SPECIFICATIONS

MODEL	DIMENSIONS	UNIT	ELECTRICAL (DUAL VOLTAGE 1 Ph/60Hz)			SHIPPING WT.
			COND. UNIT	LIGHTS	EVAPORATOR PAN	
DRF-S 4840	40"L.X33 ⁷ / ₈ "D.X48"H.	1/2	115V/16.0 AMPS	115V/2.0 AMPS	115V/ 8.3 AMPS	400 lb.
DRF-S 4848	48"L.X33 ⁷ / ₈ "D.X48"H.	3/4	230V/ 8.0 AMPS	115V/2.0 AMPS	115V/ 8.3 AMPS	450 lb.
DRF-S 4860	60"L.X33 ⁷ / ₈ "D.X48"H.	3/4	230V/ 9.4 AMPS	115V/2.5 AMPS	115V/ 8.3 AMPS	570 lb.
DRF-S 5178**	78"L.X33 ⁷ / ₈ "D.X51"H.	1	230V/14.9 AMPS	115V/3.0 AMPS	115V/ 8.3 AMPS	710 lb.
DRF-S 5194**	94"L.X33 ⁷ / ₈ "D.X51"H.	1 1/2	230V/17.4 AMPS	115V/4.0 AMPS	115V/12.4 AMPS	840 lb.

230V Units – Permanent connection to Condensing unit, Light & Evaporator pan(Optional) supplied with cord & plug
Floor drain highly recommended for these units. Front air intake ventilation grill.
****Height of base increased 3". To fit condensing unit. 51" HT available with remote condensing unit.**

STANDARD FEATURES

1. Top light.
2. Open front for complete self serve access.
3. Stainless steel shelves w/lights.
4. Stainless steel interior.
5. Solid laminate covered sides – mirrored interior sides.
6. Interior & exterior laminate finish: Black.
7. Self contained air cooled compressor

OPTIONS

1. Plastic laminate exterior finish of choice.
2. Custom units on request.
3. Remote condensing unit.
4. Condensate evaporator pan.
5. Pass thru hinged doors.

Operating temperature of 2° to 4° Celsius (37° to 40° F.) under normal store conditions of 24° Celsius (75° F.) with 50% relative humidity.
 Condensation on glass may occur under hot & humid conditions.
 Product entering the display case must be 4° Celsius (40° F.) or lower.

*Due to constant improvements, specifications are subject to change without notice.



Canadian Display Systems Inc.

177 Westcreek Drive, Woodbridge, Ontario L4L 9N6
 Ph: 905-265-7888, 1-800-895-5862 Fax: 905-265-7692
 email cds1@on.aibn.com
www.canadiandisplayssystems.com